

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
15 January 2004 (15.01.2004)

PCT

(10) International Publication Number  
**WO 2004/005161 A1**

(51) International Patent Classification<sup>7</sup>: **B65D 81/34,**  
77/22

[GB/GB]; 10 High Road, Elm, Wisbech, Cambridgeshire  
PE14 0AA (GB).

(21) International Application Number:  
PCT/GB2003/002881

(74) Agent: **CHAVE, Lynne, Fiona**; Urquhart-Dykes & Lord,  
New Priestgate House, 57 Priestgate, Peterborough, Cam-  
bridgeshire PE1 1JX (GB).

(22) International Filing Date: 4 July 2003 (04.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0215603.2 5 July 2002 (05.07.2002) GB  
0222135.6 24 September 2002 (24.09.2002) GB

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **BU-**  
**RALLS OF WISBECH LIMITED** [GB/GB]; P.O. Box  
7, Oldfield Lane, Wisbech, Cambs PE13 2SZ (GB).


(84) Designated States (*regional*): European patent (AT, BE,  
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,  
IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **SMITH, Richard**

[Continued on next page]

(54) Title: MICROWAVABLE FOOD PACKAGE HAVING A VENTING VALVE



(57) Abstract: Apparatus for enabling the alleviation of excess pressure created within a food package as a result of steam generation during cooking and more particularly microwave cooking, said apparatus comprises a product identification band (10), wrapping member (10) or label (10) which serve to encircle, partially encircle or wrap around a dish format container and/or to identify the contents of said container. The label being formed with a flap or valve through which pressure vents.

WO 2004/005161 A1

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## MICROWAVABLE FOOD PACKAGE HAVING A VENTING VALVE

This invention relates to a method and apparatus for product packaging. The invention is particularly although  
5 not exclusively applicable to packaging for products of the kind which are currently sold with a sleeve-type product identification band, wrapping member or label which serves to encircle, partially encircle, wrap around or identify a  
10 product such as a food product or so-called "ready meal" which may be contained in a dish-format container with, for example, sealant film, single layer film, flow wrap and the like covering the container. Other suitable sealant means may also be utilised such as a heat sealed laminate closing the container or rigid polypropylene lids to close the  
15 containers.

Such food products or ready meals are cooked, or more often, re-heated in a microwave oven for speed and convenience. The cooking process generates a large amount  
20 of heat in the form of steam which, if not allowed to escape, can cause the packaging to rupture, due to the increased pressure created therein by the steam. Such rupturing can cause the contents to spill into the oven and can also compromise the cooking conditions required to  
25 safely prepare the food product prior to eating. This problem is often addressed by the user being instructed to randomly pierce the sealant film to allow the steam created to escape, thereby reducing the build up of pressure within the pack.

30 However, the production of steam within such a wrapped food product can be used to produce steam cooked food products or ready meals. In this case, the random piercing of the sealant film would be inappropriate as the correct cooking

-2-

conditions may not be maintained, however a sealed container would be liable to rupture with the attendant difficulties as discussed above.

5 Previous proposals to address this problem have included the provision of a rather complex structure to act as a valve which is inserted into the sealant film. The upper surface of the valve structure is itself covered with a sealant film to prevent contamination. The disadvantages of  
10 this arrangement are that it is not unknown for the valve to fail which results in the sealant film rupturing. A further disadvantage of this system is that it is a rather complex mechanism and therefore adds to the cost and complexity of the packaging.

15

It is an object of the present invention to provide improvements in relation to one or more matters discussed herein or generally.

20 According to the invention there is provided apparatus for enabling the alleviation of excess pressure created within a food package as a result of steam generation during cooking and more particularly microwave cooking.

25 In an embodiment of the invention there is provided apparatus for enabling the alleviation of excess pressure created within a food package as a result of steam generation during cooking and more particularly microwave cooking, said apparatus comprises a product identification  
30 band, wrapping member or label which serve to encircle, partially encircle, wrap around or be placed on a dish format container and/or to identify the contents of said container and provide information relating thereto. The label comprises a backing layer carrying a release material  
35 on one face and a label layer carrying an adhesive on one

face to secure the label to the product packaging in due course, said face being adhered to the backing layer and being separable therefrom for application to a package or product in due course.

5

The product identification band or label is formed with discontinuities in the label layer which may be in the form of cuts, slots, perforations or the like which penetrate the label layer. These discontinuities may take the form of two cuts or slots which converge at a single point, or else be in the form of a single continuous cut such that a "V" shaped cut is formed although any other suitable configuration may be used such as circular oval, square etc. A fold, scored or creased line is provided between the non convergent regions of the cut or cuts such that a triangular region or flap is formed in the label layer therebetween. The arrangement of discontinuities or cuts are not, of course, limited to this particular configuration or arrangement and any suitable combination may be used.

20

The flap can be lifted or moved separably to the label layer and the fold, scored or creased line serves to impart a "hinge-like" action which assists the lifting of the flap. In addition, this region may also be embossed to a degree such that it is slightly raised from the surface of the main body of the label, this also serves to assist the lifting action of the flap. Furthermore, the embossing serves to provide a cosmetic means of locating the flap when viewing the label.

30

In a further embodiment of the invention, the regions of discontinuity which take the form of two separate cuts do not converge but are maintained separately such that the general "V" shape is maintained, although any other

35

-4-

suitable configuration may be used such as circular oval, square etc, but the cuts are separated by a portion of label material at the point at which they previously converged. The portion of label material acts to connect or  
5 "tie" the flap to the label thereby restricting movement of the flap.

In a still further embodiment of the invention, the flap may be formed from a plurality of cuts or slots which,  
10 while being arranged in a general "V" shape are separated by a region of label material thereby forming a plurality of ties.

In a still further embodiment of the invention, the region  
15 of the label having the fold, scored or creased line which serves to impart a "hinge-like" action when lifting the flap may itself be provided with cut regions or perforations which penetrate the material forming the product identification band or label.

20 When the food product or so-called "ready meal" contained in a dish-format container, is packaged, the product is sealed in the container using sealant film, a heat sealed laminate, a rigid polypropylene lid or the like is placed  
25 over the container and a small aperture such as a slot a cross or "pin prick" is made therein.

The product identification band, wrapping member or label is then applied to and adheres to the packaged product such  
30 that the region forming the flap is located over the aperture. Once the label has been applied, the contents of the container remain hermetically sealed despite the regions of discontinuity formed therein as the adhesive provided on the label layer including the flap portion

-5-

serves to retain this portion in contact with the sealant means.

When the packaged food product is heated in a microwave oven, steam is generated within the package which acts to heat and/or cook the food contained therein. When the amount of steam created within the package reaches a level at which it begins to impinge on the integrity of the sealant film, the pressure will act on the point of least resistance and this will be the aperture made in the sealant film. The steam will begin to move through this aperture as the pressure inside increases. As the aperture is covered by the label and in particular the triangular or flap portion, the steam moving through the aperture will act on the underside of the product identification band, wrapping member or label in this particular region, and the pressure of the escaping steam will cause the adhesive to be this region of the label to be overcome thus permitting the flap portion to lift and act as a valve allowing the steam to vent.

In those embodiments which are formed with ties or retaining tabs, these serve to provide additional restriction to the lifting movement of the flap as a result of pressure caused by escaping steam such that steam is able to vent from beneath the flap as the pressure begins to build and these are then overcome or broken as the pressure increases enabling the flap to lift. An advantage of the retaining ties is that these serve to prevent the flap or valve opening prematurely, for example in the event pressure builds up in the container during storage. In those embodiments of the invention in which the hinged region is formed with discontinuities in the form of cuts or perforations, these serve as further means by which steam may be vented. These embodiments provide means by

-6-

which different amounts of steam and the attendant pressure created thereby to be retained within different packs.

5 In a further embodiment of the invention, a range of adhesives of varying strengths may be applied to the product identification band, wrapping member or label for different food products. This will enable different amounts of steam and the attendant pressure created thereby to be retained within different packs before the pressure of steam will overcome the adhesive forces of the label in  
10 this area and the flap or valve is activated or lifted.

In a further embodiment of the invention there is also provided a pressure relief valve for a packaging container  
15 in the form of a product identification band or label comprising a backing layer carrying a release material on one face and a label layer carrying an adhesive on one face to secure the label to the container, said face being adhered to the backing layer and being separable therefrom  
20 for application to a package or product in due course, said label layer being formed with a valve member which, when the label is applied to the container, is disposed over an aperture formed in the container or closure/sealant means therefore. When the food product or so-called "ready meal"  
25 contained in a dish-format container, is packaged, the product is sealed in the container using sealant film, a heat sealed laminate, a rigid polypropylene lid or the like is placed over the container and a small aperture such as a slot a cross or "pin prick" is made therein.

30

The pressure relief valve in the form of a product identification band or label is applied to and adheres to the packaged product such that the valve is located over the aperture. Once the label has been applied, the contents  
35 of the container remain hermetically sealed despite the



-7-

regions of discontinuity formed therein as the adhesive provided on the label layer including the valve portion serves to retain this portion in contact with the sealant means.

5

When the packaged food product is heated in a microwave oven, steam is generated within the package which acts to heat and/or cook the food contained therein. When the amount of steam created within the package reaches a level at which it begins to impinge on the integrity of the sealant film, the pressure will act on the point of least resistance and this will be the aperture made in the sealant film. The steam will begin to move through this aperture as the pressure inside increases. As the aperture is covered by the label and in particular the valve the steam moving through the aperture will act on the underside of the label in this particular region, and the pressure of the escaping steam will cause the adhesive in this region of the label to be overcome thus permitting the valve to open allowing the steam to vent.

20

In still further embodiment of the invention there is provided a product identification band, wrapping member or label having adhesive on one face as hereinbefore described in combination with closure means for a container such as a sealant film, a heat sealable laminate, polypropylene lid or the like. The closure means is formed with an aperture therein and when the label and closure means combination are assembled, the flap formed in the label as hereinbefore described is caused to overlies the aperture.

25

30

The closure means in combination with the label having a flap which may serve as a valve formed therein is then used in the usual manner to seal a product container. This

-8-

serves to seal and apply the label to the product in one step.

5 In a further embodiment of the invention, labels are provided in which the regions of discontinuity may be provided with one or more ties which disrupt the line of the cut thereby providing regions which serve to connect or "tie" the flap to the body of the product identification band are provided in combination with closure means for a  
10 container such as a sealant film, a heat sealable laminate, polypropylene lid or the like.

In a still further embodiment of the invention, labels in which the fold, scored or creased line which serves to  
15 impart a "hinge-like" action when lifting the flap are provided with cut regions or perforations are provided in combination with closure means for a container such as a sealant film, a heat sealable laminate, polypropylene lid or the like.

20

In a further embodiment of the invention there is provided a provided a pressure relief valve for a packaging container in the form of a product identification band or  
25 label as hereinbefore described in combination with closure means for a container such as a sealant film, a heat sealable laminate, polypropylene lid or the like. The closure means is formed with an aperture therein and when the pressure relief valve and closure means combination are  
30 assembled, the valve is caused to overlie the aperture.

In a still further embodiment of the invention there is provided an adhesive self-venting label.

35

-9-

According to a further embodiment of the invention there is provided a packaged product wherein said packaging comprises a dish-like container to retain the product being packaged covered or sealed with a suitable sealant means  
5 such as a sealant film, wrap or lid. An aperture is formed in the sealant means and a label or product identification band having a flap, vent or valve means formed therein is placed on the wrapped product to complete the packaging thereon. The label is applied such that the flap or vent is  
10 located over the aperture formed in the sealant means.

According to the invention there is also provided a method of facilitating the safe removal of steam wherein during  
15 the packaging of a food product or so-called "ready meal" contained in a dish-format container. Said method comprising the step of placing a sealant film over the container, the step of making a small aperture in the sealant film and the further step of applying a product  
20 identification wrapping or label having a flap formed therein such that the flap is located over the aperture such that pressure created within the container when the ready meal is heated vents through the flap which acts as a valve.

25

Embodiments of the invention will now be described with reference to the following illustrative drawings in which:

30 Figure 1 shows a diagrammatical plan view of a label as herein before described;

Figure 2 shows a further embodiment of the label having a tie means;

35

-10-

Figure 3 shows a further embodiment of the label having a plurality of tie means;

Figure 4 shows a further embodiment of the label;

5

Figure 5 shows a diagrammatical sectional view of the label of Figure 1 in combination with closure means; and

Figure 6 shows a diagrammatical plan view of a label in which the flap or valve member is shown in an open position.

As shown in Figure 1, said apparatus 10 comprises a product identification band, wrapping member or label 10 which serves to encircle, partially encircle or wraps around a dish format container. The label 10 comprises a backing layer (not shown) carrying a release material on one face and a label layer 12 carrying an adhesive on one face to secure the label to the product packaging in due course, said face being adhered to the backing layer and being separable therefrom for application to a package or product in due course.

The product identification band or label 10 is formed with discontinuities 14 in the label layer 12 which may be in the form of cuts, slots, perforations or the like which penetrate the label layer 12. These discontinuities may take the form of two cuts which converge at a single point, or else be in the form of a single V - shaped cut. A fold, scored or creased line 16 is provided between the non convergent region 18 of the cut or cuts such that a triangular region or flap 20 is formed in the label layer 12 therebetween. In addition, the region 20 may also be embossed 22 to a degree such that it is slightly raised

-11-

from the surface of the main body of the label 12, this also serves to assist the lifting action of the flap.

5 When the food product or so-called "ready meal" contained in a dish-format container, is packaged, the product is sealed in the container using sealant film, a heat sealed laminate, a rigid polypropylene lid or the like is placed over the container and a small aperture such as a slot a cross or "pin prick" is made therein.

10

The product identification band, wrapping member or label 12 is then applied to and adheres to the packaged product (not shown) such that the triangular area 18 is located over the aperture. Once the label 12 has been applied, the contents of the container remain hermetically sealed despite the regions of discontinuity 18 formed therein as the adhesive provided on the label layer including the flap 20 portion serves to retain this portion in contact with the sealant means.

20

When the packaged food product is heated in a microwave oven, steam is generated within the package which acts to heat and/or cook the food contained therein. When the amount of steam created within the package reaches a level at which it begins to impinge on the integrity of the sealant film, the pressure will act on the point of least resistance and this will be the aperture made in the sealant film. The steam will begin to move through this aperture as the pressure inside increases. As the aperture is covered by the label 10 and in particular the triangular or flap portion 20 the steam moving through the aperture will act on the underside of the product identification band, wrapping member or label in this particular region 12, and the pressure of the escaping steam will cause the adhesive to be this region of the label to be overcome thus

35

-12-

permitting the flap portion 20 to lift and act as a valve allowing the steam to vent as shown in Figure 6.

5 In those embodiments shown on Figures 2, 3, 4 and 5 which are formed with ties or retaining tabs 22 these serve to provide additional restriction to the lifting movement of the flap 20 as a result of pressure caused by escaping steam such that steam is able to vent from beneath the flap 20 as the pressure begins to build and these are then  
10 overcome or broken as the pressure increases enabling the flap to lift.

In those embodiments of the invention in which the hinged region is formed with discontinuities in the form of cuts  
15 24 or perforations 26 as shown in Figures 5 and 6, these serve as further means by which steam may be vented.

The invention provides a simple, hygienic and cost effective way of providing a safety valve or vent in  
20 prepackaged food products to facilitate the safe removal of excess steam created during the cooking /heating process.

## CLAIMS

1. A product identification band, wrapping member  
or label which serve to encircle, partially encircle or  
5 wraps around a dish format container and/or to identify the  
contents thereof said label comprises a backing layer  
carrying a release material on one face and a label layer  
carrying an adhesive on one face to secure the label to the  
product packaging in due course, said face being adhered to  
10 the backing layer and being separable therefrom for  
application to a package or product in due course  
characterised in that said label is formed with at least  
one region of discontinuity in the label layer.
- 15 2. A label according to claim 1 characterised in  
that said region of discontinuity is in the form of a cut,  
slot, perforations or the like which penetrate the label  
layer.
- 20 3. A label according to claim 2 characterised in  
that the region of discontinuity is in the form of a single  
shaped cut or slot.
- 25 4. A label according to claim 2 characterised in  
that said region of discontinuity is in the form of at  
least two converging cuts or slots.
- 30 5. A label according to claim 3 or claim 4  
characterised in that the region of label located between  
the cuts forms a flap member movable separately to the  
label.

-14-

6. A label according to claim 5 characterised in that said flap member is provided with a fold, scored or creased region which serves to impart a "hinge-like" action assisting movement of the flap member.

7. A label according to claim 2 characterised in that said cuts are interrupted by portions of label material which act to connect the flap member to said label.

8. A pressure relief valve for a packaging container in the form of a product identification band, wrapping member or label which serve to encircle, partially encircle or wraps around a dish format container and/or to identify the contents thereof said label comprises a backing layer carrying a release material on one face and a label layer carrying an adhesive on one face to secure the label to the product packaging in due course, said face being adhered to the backing layer and being separable therefrom for application to a package or product in due course characterised in that said label is formed with at least one region of discontinuity in the label layer.

9. A pressure relief valve according to claim 8 characterised in that said region of discontinuity is in the form of a cut, slot, perforations or the like which penetrate the label layer.

10. A pressure relief valve according to claim 9 characterised in that the region of discontinuity is in the form of a single shaped cut or slot.



-15-

11. A pressure relief valve according to claim 9 characterised in that said region of discontinuity is in the form of at least two converging cuts or slots.

5        12. A pressure relief valve according to claim 10 or claim 11 characterised in that the region of label located between the cuts forms a valve member movable separately to the label.

10       13. A label according to claim 12 characterised in that said valve member is provided with a fold, scored or creased region which serves to impart a "hinge-like" action assisting movement of the valve member.

15       14. A pressure relief valve according to claim 9 characterised in that said cuts are interrupted by portions of label material which act to connect the valve member to said label.

20       15. A pressure relief valve according to any of the preceding claims in combination with sealant means for said container.

25       16. An adhesive self-venting label for application to product packaging.

30       17. A method of facilitating the safe removal of steam wherein during the packaging of a food product or so-called "ready meal" contained in a dish-format container comprising the step of placing a sealant film over the container, the step of making a small aperture in the sealant film and the further step of applying a product identification wrapping or label having a flap formed therein such that the flap is located over the aperture  
35       such that pressure created within the container when the



-16-

ready meal is heated vents through the flap which acts as a valve.

18. A packaged product wherein said packaging  
5 comprises a dish-like container to retain the product covered or sealed with a suitable sealant means such as a sealant film, wrap or lid characterised in that an aperture is formed in the sealant means and a label or product  
10 identification band having a flap, vent or valve means formed therein is applied to the sealant means such that the flap or vent is located over the aperture formed in the sealant means.

15 19. A method of facilitating the safe removal of steam wherein during the packaging of a food product or so-called "ready meal" contained in a dish-format container. Said method comprising the step of placing a sealant film over the container, the step of making a small aperture in  
20 the sealant film and the further step of applying a product identification wrapping or label having a flap formed therein such that the flap is located over the aperture such that pressure created within the container when the ready meal is heated vents through the flap which acts as  
25 a valve.

-1/3-

FIG. 1FIG. 2

-2/3-




FIG. 3




FIG. 4




FIG. 5




FIG. 6

# INTERNATIONAL SEARCH REPORT

Int. Classification No  
PCT/GB 03/02881

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B65D81/34 B65D77/22

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1 122 189 A (MORINAGA MILK INDUSTRY CO LTD) 8 August 2001 (2001-08-08) the whole document	1-19
X,P	WO 02 087993 A (HAMMER JOEL ;MICVAC AB (SE)) 7 November 2002 (2002-11-07) the whole document	1-19
X	JP 04 201879 A (KYOKO MIZOGUCHI) 22 July 1992 (1992-07-22) abstract; figures 15A-15D	1-19
X	US 4 708 249 A (EMSLANDER JEFFREY O ET AL) 24 November 1987 (1987-11-24) the whole document	1-19
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

7 November 2003

Date of mailing of the international search report

17/11/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Pernice, C

## INTERNATIONAL SEARCH REPORT

Inter Publication No  
PCT/GB 03/02881

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 432 087 A (COSTELLO ALFRED P) 11 March 1969 (1969-03-11) the whole document ----	1-19
A	WO 00 35770 A (PEDERSEN STEEN ;TRYKKO PACK A S (DK)) 22 June 2000 (2000-06-22) the whole document -----	1-19

# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/GB 03/02881

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1122189	A	08-08-2001	EP 1122189 A1	08-08-2001
			WO 9961346 A1	02-12-1999
WO 02087993	A	07-11-2002	SE 0101516 A	31-10-2002
			SE 0101881 A	31-10-2002
			WO 02087993 A1	07-11-2002
JP 04201879	A	22-07-1992	NONE	
US 4708249	A	24-11-1987	US 4664263 A	12-05-1987
			BR 8606747 A	13-10-1987
			DE 3680647 D1	05-09-1991
			EP 0227736 A1	08-07-1987
			JP 4004228 B	27-01-1992
			JP 63500094 T	14-01-1988
			WO 8700149 A1	15-01-1987
US 3432087	A	11-03-1969	NONE	
WO 0035770	A	22-06-2000	DK 9800450 Y6	22-01-1999
			AU 759368 B2	10-04-2003
			AU 5617799 A	03-07-2000
			BR 9916462 A	04-09-2001
			CA 2352815 A1	22-06-2000
			CN 1329564 T	02-01-2002
			DE 29924321 U1	05-09-2002
			WO 0035770 A1	22-06-2000
			EA 3229 B1	27-02-2003
			EP 1165399 A1	02-01-2002
			JP 2002532080 T	02-10-2002
			NO 20012592 A	27-07-2001
			PL 348514 A1	03-06-2002
			TR 200101565 T2	21-12-2001
			US 6627862 B1	30-09-2003